

YL170Wp, Yingli Solar

Yingli's 170 watt photovoltaic module is designed for large electrical power requirements. With a 25 year warranty, the YL170 has superb durability to withstand rigorous operating conditions. Ideal for grid-connected and remote power systems, the YL170 offers high usable power per square foot of solar array.

- ◆ Solar Cell: High efficiency crystalline solar cell. Even if under the weak light, the solar module can produce maximum power output.
- ◆ Tempered glass: Anti-reflecting coating and high transmission rate glass increase the power output and mechanical strength of solar module.
- ◆ EVA and TPT: Using high quality EVA and TPT to prevent destroying and water.
- ◆ Al frame: Without screw, corner connection. 6 holes on the frame can be installed easily.
- ◆ Junction box: Multi function junction box with water proof.
- ◆ Long lifetime: ≥ 25 years; Less power decrease.
- ◆ Good performance of preventing from atrocious weather such as wind and hails.
- ◆ Resisting moisture and etching effectively, not effect by geology.
- ◆ The certificate issued by international authority: ISO Quality Management system, CE, TUV, IEC.



- World-class Product and Service
- Complete Production Chain
- PV Manufacturer from China

YL170Wp, Yingli Solar

- World-class Product and Service
- Complete Production Chain
- PV Manufacturer from China

ELECTRICAL PARAMETER

| | |
|------------------------------|--------------------------|
| Module type | 170(23)P1310×990(YLDJ-3) |
| Cell | Poly-crystal silicon |
| No. of Cells and Connections | 48 in series |
| Maximum Power (Pm) | 170W±5 |
| Maximum Power Voltage (Vpm) | 23.0V |
| Maximum Power Current (Ipm) | 7.4A |
| Open Circuit Voltage (Voc) | 29.0V |
| Short Circuit Current (Isc) | 8.1A |
| Module Efficiency | 13.1% |
| Cell Efficiency | 14.5% |

(* (STC) Standard Test Conditions: 25°C, 1 kW/m², AM 1.5)

MECHANICAL CHARACTERISTIC

| | |
|---------------------|-------------------|
| Dimensions (HxWxD) | 1310×990×50mm |
| Weight | 15.4Kg(33.9Pound) |
| Area | 1.3m ² |

(Cable Length 900mm provide by clients' requirement)


TEMPERATURE COEFFICIENTS

| | | |
|-----------------------|----------------------|-----------|
| Power | T _k (Wp) | -0.45%/°C |
| Open Circuit Voltage | T _k (Voc) | -0.37%/°C |
| Short Circuit Current | T _k (Isc) | +0.10%/°C |


ABSOLUTE MAXIMUM LIMITS

| | | |
|------------------------------|------|---------|
| Max System Voltage | V | 1000 |
| Module Operating Temperature | °C | -45—+85 |
| Wind speed | Km/h | 130 |
| Noct | °C | 46±2 |


I V CURVES




INSTALLATION DIMENSIONS



cell back side



Front side



Cell back side



Left side

| | | | | |
|-------|--------------|---------------|------------------|--------|
| 3 | Junction box | Rh0501-4 | 1PC | |
| 2 | Frame | Q128,1310×990 | 1Set | |
| 1 | Cell | 156×156 | 48PCS | |
| Item | Name | Specification | Quantity | Remark |
| Brand | Yingli solar | | 170(23)P1310×990 | |



China-Tianwei Yingli New Energy Resources Co.,Ltd.

No.3055 Middle Fuxing Road, Baoding China (071051)

Tel: +86(312)8929801 8929700 Fax: +86(312)3151881

E-mail: commerce@yinglisolar.com Http://www.yinglisolar.com